

PLOTTER E SUPPORTI PER STAMBADIGITALE & TAGLIO NOHOSTRI IN CARTUCCE E A LITRO SECINALETICA - ESPOSITORY

Roberto Brofferio

00155 Roma Via R. Lepett, 37/A-8-C Tel. 052253261 Pax 0522773224

| RBBTNT-100/150 | | | |
|------------------|---|--|--|
| Product Category | Double side tape | | |
| Description | is a double-sided tape with a fleece/tissue TNT as carrier. The acrylic adhesive offers a good ageing, UV and temperature resistance. Due to the high initial tack the tape offers a good specific adhesion on nearly all materials. Especially suitable for: • Mounting of displays and cover plates. • Self-adhesive finishing of polyester, polyether, PVC and polyethylene foams. • Laminating of roll material such as felt, film and tissue. • Splicing of paper and films. | | |
| Standard height | 1500mm | | |
| Standard lenght | 50 / 100 m | | |

| Characteristic | Unit of measure | Nominal Value | Tolerance |
|------------------------|-----------------|------------------------|-----------|
| Carrier | | Fleece | |
| Adhesive | | Acrilyc modified | |
| Liner | | Silicone-paper, yellow | |
| Liner weight | gr/m² | 95 | +/- 6% |
| Adhesion | N /cm | 6 | +/- 10% |
| Thickness | mm | 0,10 | +/- 5% |
| Temperature resistance | °C | -40/+120 | |
| resistance | | | |

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous authorities.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.